

Embed-a-Tag™

Concrete Casting ID Tags



- For precast concrete products applications
- Resistant to:
 - Heat: 1000°F (538°C)
 - Chemical
 - Abrasion
 - UV Exposure
- 3" Wide (76mm) X Customized Length
- Metal with laser markable coating

- ◆ Tags mount flush to top, facings, or edges.
- ◆ Use adhesive to hold tag on form during pour OR insert into wet concrete.
- ◆ Curing permanently attaches tag to the casting.
- ◆ Better than chalk that wipes off and paper tags that tear or fall off.
- ◆ Tag remains readable after long term outdoor exposure and will not rust.
- ◆ Compatible with InfoSight's LabeLase® Printers.
- ◆ Preprinted tags are available.



Find out how easy it is to design and print your tags with a LabeLase® Metal Tag Printer & free Producer™ Software.



TEST EMBED-A-TAG™ IN YOUR PROCESS—CONTACT US FOR SAMPLES

WE BARCODE DIFFICULT STUFF. ®

Embed-a-Tag™

Technical Specifications

Industry	Precast/pre-stressed concrete
Typical Customer	Precast concrete plants
Purpose	Durable, weather proof identification for flush mounting on top or edges of precast concrete members
Resistance	Heat: 1000°F (538°C) Chemical: Highly rust resistant Moderate resistance to common chemicals Abrasion: Moderate
Sizes	Ultraviolet: Highly resistant to sunlight and fading Width: 3.0 in (76 mm) Lengths: to customer specification, not less than 1.0 in (25 mm) Typical Length: 6.0 in (152 mm)
Composition	Metal with high contrast laser-markable coatings
Available Forms	Print on-site with one of InfoSight's durable, laser metal tag printers or preprinted by InfoSight
Available Colors	White, colors by special order



Technical specifications are subject to change without notice.
Embed-a-Tag, and Producer are trademarks of InfoSight.
LabelLase and "We Barcode Difficult Stuff" are registered trademarks of InfoSight.
Copyright 2023 InfoSight Corporation