InfoSight

LabeLase® 1000 Tag Printer
Fully Automatic Desktop Printer for Coated Metal Tags

About the LL1000

- Desktop Size
- Common Power Requirements
- Marks 3" (76mm) Wide InfoSight Metal Tags
- Continuous feed from a roll *OR* feed one tag at a time
- Data input from network or manual entry
- Serial, Ethernet, or USB connections
- All common barcodes
- Free Producer™ Software is Windows compatible

The Industry Standard Durable, Reliable, Versatile and Easy to Use

Introduced in 2003, the LabeLase 1000 is heavy industry's largest selling laser-powered metal tag printer. Around the world, LL1000s are printing tags to nail on to hot steel slabs, wire onto galvanizing trays, rivet onto refinery pumps and fix to laboratory equipment, industrial engines and outdoor fixtures. They are a world standard for speed, durability and value.

- **Sharp, clear text, barcodes, logos, graphics, and user selectable fonts.**
- **Automated batch printing from a 300 ft (91 m) coil.**
- **Compact footprint for desktop or bench top use.**
- **Easy and safe operator controls.**
- **Simple maintenance routines.**

MADE IN USA

FC   C·D·R·H   FDA   CE   RoHS

DANGER
LASER RADIATION, AVOID EYE OR SKIN EXPOSURE
TO DIRECT OR SCATTERED RADIATION
30 WATTS CO2 MAX
0.57 - 10.63 UM
WAVE LENGTH -
CLASS 1 LASER
PRODUCT

LabeLase® 1000 Tag Printer

Technical Specification

Dimensions	23"D x 14"H x 10"W (59 x 36 x 26 cm) including spool
Net Weight	40 lbs. (< 18 kg)
Power	120 - 240 VAC, 50/60 Hz, 2.4A
Tag Feed	Continuous roll or single tag
Data Input	Manual or network
Maximum barcode length	Up to 24 in (610 mm)
Tag Width	3.0 in (76 mm)
Barcodes Per Tag	Unlimited, within available space
Barcode Symbology	Supports most common 1D/2D barcodes. Custom or proprietary symbology can be developed
Tag Composition	InfoSight metal tags with laser-markable coatings
Communications Interface	**PC to Printer:** RS232C Serial, USB or Ethernet **Host to PC:** InfoSight Extended Protocol, File Transfer and Ethernet
Tag Layout Software	Producer™ software included free. Windows Compatible: 7, 8, 8.1 & 10 (32/64 bit)

FC CDRH FDA CE RoHS

DANGER
LASER RADIATION, AVOID EYE OR SKIN EXPOSURE
TO DIRECT OR SCATTERED RADIATION
30 WATTS CO2 MAX
0.57 - 10.63 UM
WAVE LENGTH -
CLASS 1 LASER
PRODUCT