



Pic-Anneal®

Tags for Rod and Wire Processors



Pic-Anneal® Specifications:

| | |
|-------------------------|---|
| Industry | Metal rod and wire processing |
| Typical Customer | Rod mills; Wire mills; Wire processing plants; Fabricators; Anodizers; Metals service providers |
| Purpose | Tracking finished and unfinished work pieces through the entire pickling and annealing process |
| Resistance | Heat: 1800°F (982°C) for 2 hours; 1700°F (926°C) for up to 48 hours. Chemical: 180°F (82°C) in 20% H2SO4 for 2 hours; or 100°F (38°C) 24% HCL for 2 hours. |
| | Abrasion: Moderate |
| | Ultraviolet: Highly resistant to sunlight and fading |
| Sizes | Width: 3.0 in (76 mm) Lengths: to customer specification, not less than 1.0 in (25 mm) Typical Lengths: 6.0 in (152 mm) |
| Composition | Metal with high contrast laser-markable coatings |
| Available Forms | Pre-printed by InfoSight or print on-site with one of InfoSight's durable, laser metal tag printers |
| Available Colors | Standard white, colors by special order |

Pickle and Anneal - One Tag for the Whole Process

InfoSight tags are known for their ability to handle high temperatures. The Pic-Anneal tag gives rod mills, wire mills and foundries a way to track parts through the entire pickling and annealing process - both acid baths and annealing heat.

- ◆ Readability after descaling acid baths and extended annealing cycles.
- ◆ Reduced handling for greater productivity and worker safety.
- ◆ Error-free shipping after treatment.
- ◆ Test Pic-Anneal in your own process: call today for samples.



Printers & Tags that Cut Costs, Increase Safety and Ensure Traceability