

CA-Tag[™]

Forge and Foundry Tag



- For Applications in specialty annealing of steel, copper, & alloys.
- To track materials heat treated in oxygen-free furnaces.
- Resistant to:
- Heat: up to 1800°F (982°C) see reverse for details.
- Chemicals.
- Abrasion.
- UV Exposure.
- 3" Wide (76mm) X Customized Length.
- Steel with laser markable coating.
- The only barcodable tag designed to survive in oxygen-free, contaminant-free annealing ovens.
- For use with carbon steel, stainless steel, coper, & exotic alloys.
- Wide variety of attachment options.
- High contrast alphanumerical characters, logos, and 1D & 2D barcodes.
- Tags are printable with InfoSight LabeLase® Laser Metal Tag Printers.
- Preprinted Tags Available.



Find out how easy it is to design and print your tags with a LabeLase® Metal Tag Printer & free ProducerTM Software.



TEST CA-TAG IN YOUR FURNACE—CONTACT US TODAY.

CA-Tag[™]

Technical Specifications

Industry	Specialty annealing for steel, copper and alloys
Typical	Operators and users of oxygen-free annealing
Customer	furnaces
Purpose	Tracking materials heat treated in oxygen-free
	furnaces
Resistance	Heat: 1800°F (982°C) for 2 hours; 1600°F (871°C)
	Up to 48 hours and multiple cycles
	Chemical: Common cleaners and solvents
	Abrasion: Moderate
	Ultraviolet: Highly resistant to sunlight and fading
Sizes	Width: 3.0 in (76 mm)
	Lengths: to customer specification, not less than 1.0
	in (25 mm)
	Typical Lengths: 4.0 in (102 mm)
Composition	Steel with high contrast laser-markable coatings
Available	Print on-site with one of InfoSight's durable, laser
Forms	metal tag printers or pre-printed by InfoSight.
Available	White, colors by special order
Colors	

