

PaintTag[™]

Tags for Fabricators and Metal Painting Contractors



- For applications where fabricators are identifying pieces before, during, and after painting
- Resistant to:
 - Heat—1000°F (538°C)
 - Chemical
 - Abrasion
 - UV Exposure
- 3" (76mm) Wide X Customized Length
- Metal substrate with laser markable coatings

- ◆ PaintTag[™] is ideal for tracking work pieces through acid prep and painting operation.
- Increase efficiency & reduce handling—tags are applied once and are readable throughout the process.
- Traceability & error proof installations.
- Printable with InfoSight LabeLase® Metal Tag Printers.
- Preprinted tags are available.



Find out how easy it is to design and print your tags with a LabeLase® Metal Tag Printer & free ProducerTM Software.



PROCESSES VARY—CONTACT INFOSIGHT FOR FREE TEST SAMPLES.

PaintTag[™]

Technical Specifications

| Industry | Metals fabrication |
|---------------------|--|
| Typical Customer | Fabricators, electrostatic painting service providers |
| Purpose | Tracking in-process assemblies and lots through chemical cleaning and painting |
| Resistance | Heat: Contact InfoSight for more details |
| | Chemical: Resists most common acid and caustic |
| | rinses, paints, epoxies and lacquer |
| | Abrasion: Moderate |
| | Ultraviolet: Highly resistant to sunlight and fading |
| Sizes | Width: 3.0 in (76 mm) |
| | Lengths: to customer specification, not less than 1.0 in (25 mm) |
| | Typical Lengths: 3.0 in (76 mm) |
| Composition | Metal, with high contrast laser-markable coatings |
| Available | Print on-site with one of InfoSight's durable, laser |
| Forms | metal tag printers or pre-printed by InfoSight |
| Available Colors | Standard white only, colors available by special order |



Use the QR code to learn about all of our fabricator tags:

Kettletag® PLUS
PaintTagTM

ShotTag[™]
PowderCoat[™]Tag

